DATA SHEET





Elegant Trio 19inch Free Standing Rack Cabinet H:42U W:800 x D:800

- Hinged Glass Double Opening Front Door Metal Side Frames
- Metal single rear door
- Optional perforated front and rear doors
- Removable and lockable side doors
- Optional fan-unit into the roof or 19inch rack mount type fan unit
- Bottom case with cable entry with sliding cover
- 2 sets of 19" mounting rails are adjustable throughout the entire depth of the cabinet, multi folded 1,50mm thickness
- High load carrying capacity (standard 600kg)

List Code : ELGT42U8080BL211MF2DF0P1

Technical Data

Dimensions HxWxD in mmH:1955mm W:800mm D:800mm (Check 2nd page for different height options)Height in U42UColorRAL 9005 Black color = ELGT42U8080BL211MF2DF0P1Grounding countinuityIn accordance with the standard EN 61587-1: 2012 / EN 61010-1 / IEC 60917- IEC 60297StandardsISO9001-2015TS EN 61587-1 :2012, 5.2.1 and 5.2.2CE According the IEC/ISO 17050 & EN 60335-1

Mechanical Characteristics


| Material | Sheet Steel, TS EN 10130 :2006 |
|------------------------|--------------------------------|
| Inside height in mm | 1870,10 |
| Outside height in mm | 1955 |
| Load Carrying Capacity | 600kg / 1322lbs |
| IP rating | IP20 |

We are responding the needs of users with choice of 5 different height dimensions.

Height : 42U Width : 800mm Depth : 800mm

DATA SHEET






| ELEGANT TRIO 800 x 800 mm | | | | | | | |
|---------------------------|--|--------------------|--------------------|--------------------------------|------------------------------|--|---|
| Product Code | Product Description | Width (W) mm | Depth (D) mm | H:1 Inner Height (mm) | H:2 Out Height (mm) | (H:3) Out height with levelling feet | H:4 Out height with caster set |
| ELGT42U8080BL211MF2DF0P1 | Elegant Trio 19" 42U W=800 mm D=800 mm | 800 | 800 | 1870,1 | 1955 | 1985 | 2035 |

DATA SHEET



Explode View



*Fan unit and caster set must be ordered separately.




VENTILATION OPTIONS

STANDARDS: EMC EN55032:2015 & LVD IEC 62368-1 :2018

Power Characteristics

| Voltage range | |
|----------------------|--|
| Freq Hz | |
| Current (A) | |
| Power W | |
| Speed RPM | |
| Noise level in (dB) | |
| Air flow M3/Hr & CFM | |


220/240 50/60 0,14A 22 2700/3000 40/47dB 133/162 & 82/95




Compatible Fan Units

| PACCELGFN02 | Ventilation unit with 2 Fans+with On/Off switch control |
|------------------------------|---|
| PACCELGFN04 | Ventilation unit with 4 Fans+with On/Off switch control |
| PACCELGFNT2 | Ventilation unit with 2 Fans+Analog Thermostat |
| PACCELGFNT4 | Ventilation unit with 4 Fans+Analog Thermostat |
| PACCELGFNDT2 PACCELGFNDT4 | Ventilation unit with 2 Fans+Digital Thermostat Ventilation unit with 4 Fans+Digital Thermostat Note: compatible with all 19inch rack mount Fan units |

SHALVES






Front view Fixed & Sliding shelf installation



PACCRKSR80 PACCRKHR80 1/2U Fixed Shelf - 800 mm Depth Cabinets Sliding Shelf - 800 mm Depth Cabinets

Note: compatible with all cantilever shalves



FIXED /SLIDING SHELVES LOAD CARRYING CAPACITIES

- Fixed shelf : 50kg / 110lbs
- Sliding shelf : 25kg / 55 lbs

Rear view Fixed & Sliding shelf installation

HEAVY DUTY TYPE FIXED /SLIDING SHELVES LOAD CARRYING CAPACITIES

- HD Fixed shelf : 100kg /220lbs
- HD Sliding shelf: 66kg / 145lbs

*Important: Fan units and shelves are not including, please order separately.




ELEGANT TRIO OPSIYONLARI

| Institutional Coding Initial Character | U Height | Width- Depth Dimension | Color Code | | D | oor Options | |
|--|-------------|------------------------------|-----------------|----|---|---|--|
| ΑΑΑΑ | xxu | WWDD | сс | | x | Х | х |
| | ~~0 | WWWDD | | | FRONT DOOR | REAR DOOR | SIDE PANEL |
| ELGT | 20U | 6060 | RAL9005 WRY | BL | 1 Hinged Glass Single Opening Front Door Metal Side Frames | 1 Removable Rear Door | 0 No Side Panels |
| | 26U | 6080 | RAL 7035 WRY | LG | 2 Hinged Glass Double Opening Front Door Metal Side Frames | 2 Hinged Metal Double Opening Rear Door | 1 Removable Side Panel |
| | 32U | 6010 | | | 3 Hinged %85 Curved Perforated Single Opening Front Door | 3 Hinged Metal Single Opening Rear Door | 2 Removable Side Panel with Louver |
| | 36U | 8080 | | | 4 Hinged %85 Flat Perforated Double Opening Front Door | 4 Hinged %85 Flat Perforated Double Opening Rear Door | 3 Removable %80 Flat Perforated Side Panel |
| | 42U | 8010 | | | 5 Hinged %80 Curved Perforated Single Opening Front Door | 5 %Removable %80 Flat Perforated Rear Door | |
| | | | | | 6 Hinged %80 Flat Perforated Double Opening Front Door | 6 Hinged %80 Flat Perforated Double Opening Rear Door | |
| | | | | | 7 Hinged Metal Single Opening Front Door | 9 Hinged %80 Flat Perforated Single Opening Rear Door | |
| | | | | | 8 Hinged Metal Double Opening Front Door | | |
| | | | | | 9 Hinged %80 Flat Perforated Single Opening Front Door | | |
| | | | | | A Hinged Full Framed Glass Single Opening Front | | |
| | | | | | B Hinged %85 Flat Perforated Single Opening Front Door | | |
| | | | | | C Hinged Full Framed Glass Double Opening Front Door | | |



ELEGANT TRIO FRONT DOOR OPTIONS





ELEGANT TRIO REAR DOOR OPTIONS

